



Designation IEC	LR6
System	Zn-MnO <sub>2</sub> (Alkaline)
Shelf Life (Coding)*	10 years
Nominal Voltage [V]	1.5
Typical Capacity C [mAh]	2960 (discharge with high-resistance)
Permissible Temperature Range	- 20 °C ... 50 °C
Weight, approx. [g]	23,8
Volume [ccm]	7.5

Dimensions [mm] min: max:

Ø	13.5	14.5
A	-	50.5
B	49.2	-
C	7.0	-
E	-	0.5
F	-	5.5
G	1.0	-

### Typical Capacities (at 20°C)



Discharge Type	Load	End Voltage[V]	0.9
1H/D, 7D/W	250 mA	Time [h]	9,1
CD / MD / Electronic game		Capacity [mAh]	2281
		Energy [mWh]	2731
Discharge Type	Load	End Voltage[V]	0.8
1H/D, 7D/W	3.9 Ω	Time [h]	8.5
Motor / toy		Capacity [mAh]	2454
		Energy [mWh]	2811
Discharge Type	Load	End Voltage[V]	0.9
4H/D, 8D/W, 7D/W	3.3 Ω	Time [h]	408
Portable Lighting		Capacity [mAh]	2453
		Energy [mWh]	2978

**No publication or circulation of data to third parties without consent of VARTA Consumer Batteries**

\* In consideration of typical loss of capacity at storage and application.